





Equipment Program: Product comparison  
Powered Wheelchairs - Rear Wheel Drive

All specifications and  
features listed are standard

Product Name	A200			R44			Torque			Quickie Explore			
													
Type / Variant	1 - Adult	2 - Adult	3 - Adult	4 - Adult	2 - Paed	3 - Paed	4 - Paed	2 - Adult & Paed	3 - Adult & Paed	4 - Adult	4 - Paed		
Local Supplier	Aidacare	Equip4Living / Aidacare	Equip4Living / Aidacare	Aidacare	Equip4Living / Aidacare	Aidacare	Aidacare	Invacare	Invacare	Invacare	Aidacare		
Seating (mm)													
Seat Width	380-420, 430-480			355-460, 405-510, 510-610			255-355, 355-460		355-460		305-405, 405-510, 510-610	405-510, 510-610	
Seat Depth	380-460, 420-500			355-460, 405-510, 510-610			255-355, 355-460		355-460		305-460, 405-480, 480-610	405-480, 480-610	
Front Seat to Floor Height	430, 480	400-455	435-490		400-455	435-490		445, 500, 535		450, 475, 500		420mm	
Backrest height	430-635 (not adj)			430-635 (not adj)			430-635 (not adj)		305-610		405-660	510-660	305-510 (not adj)
Backrest Options	tension adj, -9, 1,11,21 deg OR 0,10,20,30 deg	85-12- deg (5 deg inc)		min sheer reclining back	85-12- deg (5 deg inc)		min sheer reclining back	85-105 deg (5 deg inc)		min sheer reclining back	min sheer reclining back		
Armrests	single post, removable, height adjustable	Removable, single post, height adj, HD (205-305, 255-355), desk or full length, straight or waterfall		Reclining, flip back (200-230, 255-280), desk / full length	Paediatric removable		Reclining, flip back (200-230, 255-280), desk or full length	flip up and removable height adj, Australian T-arms, desk or full length		reclining height adj, desk or full length	height adj cantilever or dual post, or reclining flip up, desk or full length		
Legrests	swing away,	70 deg swing away			Paediatric swing away (180-255)			70 deg swing away hanger bracket or				Paediatric swing	
Footplate	plastic	Angle adj, range of sizes			Angle adj (125-150)			Adj angle flip up, extra large alum				angle adj, range of	
Power Positioning		Tru balance tilt 55deg.	Tilt 55 deg and recline 168 deg.		Tru balance tilt 55deg.	Tilt 55 deg and recline 168 deg.		Tilt 55 deg		Tilt 55 deg and recline 170	Tilt 50 deg and recline		
Accessories (extra cost)	arm pads, stump support, elevating legrests, footrests	armrest options, legrest options, elevating leg rests			armrest options, legrest options, elevating leg rests			armrest options, elevating legrests,				armrest, legrest and power options	

## Equipment Program: Product comparison Powered Wheelchairs - Rear Wheel Drive

All specifications and features listed are standard

Base					
Overall Width	570mm	641mm	641mm	630mm	635mm
Overall Length (no foot riggings)	770mm	880mm	880mm	710mm	1105mm (overall)
Castor size	8"	10" Pneumatic, 9"*** 14"	9" or 10" pneumatic		8" pneumatic
Drive wheel size		14"Pneumatic or Solid	14" pneumatic	350mm	14" pneumatic
Ground clearance		82.5mm at battery tray	82.5mm at battery tray		95mm
Motor Package	2 pole 6kph	4 pole 9.6kph motor	4 pole 9.6kph motor	4 pole	4 pole 10kph
Electronics Technologies	P&G VR2	Q-logic	Q-logic	Mk6i MPJ Expandable Controller, 90 Amp G-Trac std	90Amp R-net Intelli-drive std
Load capacity	100kg	136kg	136kg	136kg, 181kg HD**	181kg
Testing	AS, Crash testing	AS, Crash testing	AS, Crash testing	AS, Crash testing	AS, Crash testing
Clinical considerations					